

SHOWA

477



Full nitrile coating combined with nitrile foam on palm on polyester/nylon/insulated acrylic liner

[FEATURES

- EN 407:2004 Contact heat Level 2; contact temperature up to 250 °C (482 °F) for 15 seconds
- Dual nitrile coating technology, extra coating on palm
- Seamless knit
- Fixed acrylic terry liner
- Anatomical hand shape design

[BENEFITS

- Insulated liner protects provide barrier from cold ensuring warmth and comfort all day long
- Fully double engineered coating protects against liquids and water penetration Impermeable for working in damp or greasy environments, keeps your hand dry
- Dual nitrile coating technology provides optimal grip longevity
- Highly flexible and resistant to abrasion and tearing
- Replicates the natural curvature of human hand and so reduces hand fatigue

[INDUSTRY



Airports & Ports



Construction



Municipal Services



Oil and Gas



Railways



Utilities



Warehousing & Distribution

[IDEAL APPLICATIONS

- Cementing
- Concreting
- Concrete pouring
- Demolition
- Drainage, piping
- Machine driving
- Maintenance
- Mortar
- Painting
- Roofing application membranes
- Sanding
- Slingers & signaller
- Tile setting
- Washing & cleaning
- Drilling
- Heavy equipment handling
- Pipe Fitters



MATERIAL

- Fixed insulated acrylic
- Nylon
- Polyester
- Seamless knit

COATING

- Foam nitrile
- Nitrile



NORMS



SHOWA 477



PACKAGING

- 5 Pair per polybag
- 12 Polybags per case
- 60 Pair per case



SIZES

- 7/M
- 8/L
- 9/XL
- 10/XXL



COLOUR

- Blue w/ black coating



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA 376R



MATERIAL
Seamless knit
COATING
Nitrile
CATEGORY
General Purpose

SHOWA 377



MATERIAL
Nylon
COATING
Foam nitrile
CATEGORY
General Purpose

SHOWA 379



MATERIAL
Cotton
COATING
Foam nitrile
CATEGORY
Chemical

SHOWA 377-IP



MATERIAL
Nylon
COATING
Foam nitrile
CATEGORY
Impact

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, high-temperature or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. This glove is designed for an intense activity down to 0°C. Designed to protect at temperature down to -30°C, for short or intermittent contact.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved