

Product Datasheet model skyper 9195 275



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Ergonomical design * Impact protection up to grade F * Integrated brow, side and cheek guards * Extremely simple lens replacement * Good field of vision * Soft temple end with spring effect * 5 position length adjustability * Adjustable side piece inclination
<p>Technical details</p> <p>Frame</p> <p>Material</p> <p>Colour</p> <p>Material</p> <p>Features</p> <p>Colour</p> <p>Material</p> <p>Features</p> <p>Colour</p>	<p>Front piece</p> <p>TPU</p> <p>black</p> <p>Side piece</p> <p>PC</p> <p>5 position length adjustability</p> <p>black</p> <p>Temple</p> <p>PP</p> <p>Soft-temple end</p> <p>black</p>

Lens	
Material	PC
Thickness	1,85 mm
Filter	2-1,2 according to DIN EN 170
Coating	supravision HC-AF
Colour	clear
Optical class	1
Impact resistance	F (45 m/s) according to DIN EN 166
Miscellaneous	
Weight	31 g
Packing	5 spectacles per box 200 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170