

Solo 992

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 24
- **Thickness (mm)** 0.10
- **Wrist** Rolled cuff
- **Colour/Color** Natural
- **Interior finish** Powdered
- **Exterior finish** Smooth
- **Size / EAN** 6 7 8 9
- **Packaging** 100 gloves/box - 1000 gloves/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

Legends

ANSI	CUT RESISTANCE		
	A1 ≥ 200 G	A4 ≥ 1500 G	A7 ≥ 4000 G
	A2 ≥ 500 G	A5 ≥ 2200 G	A8 ≥ 5000 G
CUT	A3 ≥ 1000 G	A6 ≥ 3000 G	A9 ≥ 6000 G

EN 511	COLD HAZARDS
	PERFORMANCE LEVELS
	0-4 0-4 0 or 1
	Water permeability
	Contact cold resistance
	Convective cold resistance

EN 407	THERMAL RISKS
	Heat and fire
	PERFORMANCE LEVELS
	0-4 0-4 0-4 0-4 0-4 0-4
	Resistance to large quantities of molten metal
	Resistance to small drops of molten metal
	Radiant heat resistant
	Convective heat resistance
	Contact heat resistance
	Burning behaviour

PROTECTION FROM PESTICIDES

ISO 18889	ISO 18889	ISO 18889
G1	G2	GR

MICRO-ORGANISMS

EN ISO 374-5	EN ISO 374-5
Protection against bacteria, fungi	Protection against bacteria, fungi, virus
	VIRUS

CHEMICAL RISKS

EN ISO 374-1	EN ISO 374-1	EN ISO 374-1
Type A	Type B	Type C
U V W X Y Z	X Y Z	
A Methanol	J n-Heptane	
B Acetone	K Sodium hydroxide 40%	
C Acetonitrile	L Sulphuric acid 96%	
D Dichloromethane	M Nitric acid 65%	
E Carbon Disulfide	N Acetic acid 99%	
F Toluene	O Ammonia 25%	
G Diethylamine	P Hydrogen peroxide 30%	
H Tetrahydrofuran	S Hydrofluoric acid 40%	
I Ethyl acetate	T Formaldehyde 37%	

RADIOACTIVE
CONTAMINATIONELECTROSTATIC
DISCHARGE PROTECTION

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS
0-4 0-5 0-4 0-4 A-F (P)
Impact protection
Cut resistance according to ISO 13997
Puncture resistance
Tear resistance
Blade cut resistance
Abrasion resistance

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Excellent dexterity thanks to flexibility of natural latex.
- Easy to put on and take off.
- Protection adapted to short duration usage.

MAIN FIELDS OF USE

Automotive/mechanical industry

- Assembly of small, oil and grease free parts

Health

- Common Tasks in hospitals and clinics

Laboratory

- Manufacturing of medicines
- Pharmaceutical preparation
- Research, analysis, handling of precision parts

INSTRUCTIONS FOR USE

Instructions for use

- It is not recommended to persons sensitized to natural latex, thiazoles and dithiocarbamates to use these gloves .
- Put the gloves on dry, clean hands.
- Position the cuff over the garment to prevent penetration of a liquid.
- These gloves are designed for single use only.
- Do not touch the external side of the gloves when taking them off. Fold back the cuff end and pull them off while turning them inside out.

Storage conditions

- Store the gloves in their original packaging protected from light, humidity, and far from heat sources and electrical equipment.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/07/19/2013
- **Issued by the notified body nr** : C.T.C - 4 rue Hermann Frenkel - F- 69367 LYON Cedex 07
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS