

Solo 999

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (cm)** 29,5
- **Thickness (mm)** 0.10
- **Colour/Color** White
- **Interior finish** Chlorinated
- **Exterior finish** Smooth with pebbled fingertips
- **Size / EAN** 6 7 8 9
- **Packaging** 100 gloves/box - 1000 gloves/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



VIRUS



JKT

Dexterity EN 420 : 5/5

Legends

ANSI	CUT RESISTANCE		
	A1 ≥ 200 G	A4 ≥ 1500 G	A7 ≥ 4000 G
	A2 ≥ 500 G	A5 ≥ 2200 G	A8 ≥ 5000 G
CUT	A3 ≥ 1000 G	A6 ≥ 3000 G	A9 ≥ 6000 G

EN 511	COLD HAZARDS
	PERFORMANCE LEVELS
	0-4 0-4 0 or 1
	└ Water permeability
	└ Contact cold resistance
	└ Convective cold resistance

EN 407	THERMAL RISKS
	Heat and fire
	PERFORMANCE LEVELS
	0-4 0-4 0-4 0-4 0-4 0-4
	└ Resistance to large quantities of molten metal
	└ Resistance to small drops of molten metal
	└ Radiant heat resistant
	└ Convective heat resistance
	└ Contact heat resistance
	└ Burning behaviour

PROTECTION FROM PESTICIDES

ISO 18889	ISO 18889	ISO 18889
G1	G2	GR

MICRO-ORGANISMS

EN ISO 374-5	EN ISO 374-5
Protection against bacteria, fungi	Protection against bacteria, fungi, virus
	VIRUS

CHEMICAL RISKS

EN ISO 374-1	EN ISO 374-1	EN ISO 374-1
Type A	Type B	Type C
U V W X Y Z	X Y Z	
A Methanol	J n-Heptane	
B Acetone	K Sodium hydroxide 40%	
C Acetonitrile	L Sulphuric acid 96%	
D Dichloromethane	M Nitric acid 65%	
E Carbon Disulfide	N Acetic acid 99%	
F Toluene	O Ammonia 25%	
G Diethylamine	P Hydrogen peroxide 30%	
H Tetrahydrofuran	S Hydrofluoric acid 40%	
I Ethyl acetate	T Formaldehyde 37%	

RADIOACTIVE
CONTAMINATIONELECTROSTATIC
DISCHARGE PROTECTION

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS
0-4 0-5 0-4 0-4 A-F (P)
└ Impact protection
└ Cut resistance according to ISO 13997
└ Puncture resistance
└ Tear resistance
└ Blade cut resistance
└ Abrasion resistance

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Excellent dexterity thanks to reduced material thickness.
- Easy to put on and take off.
- Recommended for persons sensitized to natural rubber proteins.
- Previous name: Solo Ultra 999

MAIN FIELDS OF USE

Automotive/mechanical industry

- Assembly of small oily parts

Aeronautics industry

- Work with composite materials (resins)

Laboratory

- Manufacturing of medicines
- Pharmaceutical preparation
- Research, analysis, handling of precision parts

INSTRUCTIONS FOR USE

Instructions for use

- It is not recommended to persons sensitized to dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- These gloves are designed for single use only.
- Do not touch the external side of the gloves when taking them off. Fold back the cuff end and pull them off while turning them inside out.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources.

Food contact US

- FDA 21CFR 177.2600

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/02/19/0584- Ext 01/02/19 Update 01-28/02/2020
- **Issued by the notified body nr** : 0075 -C.T.C- 4 rue Herman FRENKEL-F -69367 LYON CEDEX 07
- **Quality assurance certificat** : 0334- Asqual - 14 rue des Reculettes - 75013 Paris - France