

RO13090 Flamebuster Nordic Coverall



TICKING ALL BOXES

PROTECTION LEVEL: ARC 2

8.1 cal/m²

Above shown is the ATPV value.

BODY BURN INJURY PREDICTION

2.6%

EN SAFETY STANDARDS



EN ISO 13688:2013







A1 A2 Class 2 (A1 A2=50 washing cycles)




EN ISO 11612:2015 A1 A2 B1 C2 D0 E3 F1 (A1 A2=50 washing cycles)



IEC 61482-2:2009 ATPV 8.1 cal/cm2 Class 1

Body burn injury prediction



Visit www.roots-original.com/burn-injury-predictions for more information.

QUICK DETAIL OVERVIEW

Available colours

Navy Red Orange Royal **Product code** Sizing

Fabric weight

RO13090

Coverall: 350 g/m² UK36 - UK60

Inside leg length

Short: 29"

Regular: 31" $33^{\prime\prime}$ (standard size) Tall:



RO13090 Flamebuster Nordic Coverall

FEATURES & BENEFITS

Flame retardant retroreflective tape > 2-tier knee pockets

Central YKK zipper closure, top press studs > Secure closure

- 2 Chest pockets with YKK zip and flap > Double storage
- 2 Back pockets with flap > Great storage, easy access
- 2 Side pockets with trouser access > Double leg storage

Rule pocket on right leg > Convenient space for a rule

Pen pocket with flap on left sleeve > Keep your pen in place

KEY FEATURES







Freated fabric

YKK center zippe

standard



Triple stitched

FABRIC INFORMATION

Fabric composition

FLC350 - 99% cotton / 1% antistatic

Fabric weight

350 g/m²

FR Fabric Type

Treated

Additional certification





Logo

Certified for logo applications

- 1. Oeko-Tex Standard 100
- AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

- 1. Always launder with coverall zippers closed.
- 2. Remove all tools from pockets
- 3. Rinse properly after wash.
- 4. Never wash flame retardant clothing with detergents containing bleach.
- After washing, tumble dry at 50°C to avoid excessive shrinkage.
- Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit ${\it www.roots-original.com/product-care}$



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com