

Sporting sleek lines and a single-piece panoramic lens, SESTO™ safety glasses offer excellent optical quality alongside a modern design.

The slimline temple design boosts comfort when worn with ear defenders.

SPECIAL FEATURES

- ✓ Slim temples enhance comfort when worn with defenders
- ✓ Single panoramic lens
- ✓ Universal nose bridge
- ✓ Flexible TPE temple ends enhance grip and comfort
- ✓ Integral temple tip slot aids the attachment of hang cords
- ✓ Frame colours change with lens tint options
- ✓ Supplied with a microfibre storage pouch
- ✓ Weight: 28g
- ✓ 10.5 Base lens



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	● RLY00121	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	TECTON 400™ K&N Anti-scratch and Anti-fog / UV400 / Moisture repellent
AMBER	● RLY00123	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	
GREY	● RLY00122	5-2.5 e 1FTKN CE	e EN 166 FT CE	Impacts, UV and Solar radiations	
BLUE	● RLY00124	2-1.4 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	

See overleaf for this product's technical specification

GENERAL SPECIFICATION

LENS BASE	10.5mm
WEIGHT	28g

PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece moulded lens with side protection
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	Polycarbonate/Thermoplastic Elastomers (TPE)	Co-injected - Robust, flexible, lightweight with ventilated tips
HINGE	Polycarbonate/Metal	Increased strength

LENS MARKINGS

LENS FILTER TYPE:

2, 2C UV
5 Solar

SCALE NUMBER (SHADE):

1.2 Clear or Amber
1.4 Blue or I/O Waterproof
2.5 Grey

ⓔ Identity of manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

K Resistance to scratches by fine particles
N Resistance to fogging

ⒸⒺ Certification mark

FRAME MARKINGS

ⓔ Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

ⒸⒺ Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

