



## Provoq® CE ANSI CSA



RUBBER  
NOSEPIECE



RUBBER  
TIPS

Soft nosepiece

Rubber temples

Part No.	Lens and Temples
ES20C ●●●	Clear
ES20G ●●●	Gray
ES20A ●●●	Amber

### General Specifications

Weight: 24.9 gm  
PD: 64 mm  
Bridge: 16.66 mm  
Lens base: 9 curve  
Lens size diagonal: 79.83 mm  
Lens size vertical: 41.12 mm  
Lens thickness: 2.4 mm  
Overall length (lens - tip): 158 mm  
Overall width (hinge - hinge): 136 mm  
Closest point between temple tips: 79.35 mm  
Closest point between lens: 8.18 mm

Part No.	Lens Markings	Temple Markings
ES20C	2-1.2 P 1F CE	P EN 166 CE
ES20G	5-3.1 P 1F CE	P EN 166 CE
ES20A	2-1.2 P 1F CE	P EN 166 CE

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter

5 or 6: Solar filter

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark

N: Filter with anti-fog

CE: Europe standard

### Materials

Lens: polycarbonate

Temples: polycarbonate

Hinge: polycarbonate

Screw: plated steel

Temple Tip: thermoplastic rubber (TPR)

Nosepiece: thermoplastic rubber (TPR)



### Frame Marking Symbols

#### Symbols

CE: Europe standard

P: Manufacturer's mark

EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact

