



## PMXTREME® CE ANSI



RUBBER NOSEPIECE



INCLUDES STRAP



RUBBER TIPS

Built-in rubber nosepiece

Ventilated flexible temples with rubber temple tips

Includes black lanyard cord

### Part No.

### Black Frame with Cord

ES30CTM ●●	AF	Clear
ES30GTM ●●	AF	Gray



### General Specifications

Weight: 27 gm  
 PD: 72 mm  
 Bridge: 14 mm  
 Lens base: 9 curve  
 Lens size diagonal: 78 mm  
 Lens size vertical: 46 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 103 mm  
 Overall width (hinge - hinge): 140 mm

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 K: Resistance to surface damage by fine particles  
 N: Filter with anti-fog  
 CE: Europe standard

### Materials

Lens: polycarbonate  
 Temple: nylon  
 Frame: nylon  
 Screw: stainless steel  
 Nosepiece: rubber  
 Temple tips: rubber

### Part No.

### Lens Marking

### Temple Marking

ES30CTM	2 - 1.2 P 1 F K N CE	CE P EN166 F
ES30GTM	5 - 3.1 P 1 F K N CE	CE P EN166 F



### Temple Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact



All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) standards.