PRODUCT SPECIFICATION & TECHNICAL DATA

PW40 - Classic Ear Defenders

Collection: Ear Muffs
Range: Hearing Protection
Materials: ABS, Polycarbonate, PVC
Outer Carton: 48



Product information

Lightweight and robust, the PW40 is suitable for all day comfort. Excellent attenuation rate. Metal-free design.

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

EN 352-1 (SNR 27dB)
ANSI S3.19 (NRR 22dB)
AS/NZS 1270 (SLC(80) 28dB - Class 5)

Features

- Best selling style year after year
- Ultra light and compact ear muff
- Classic design ear muff
- Adjustable length for a secure and comfortable fit
- SNR 27dB attenuation level
- Light and robust
- 100% Metal Free
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- CE certified
- CE-CAT III

PRODUCT SPECIFICATION & TECHNICAL DATA

PW40 - Classic Ear Defenders
Commodity Code: 3926909790

Test House
BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
John M. Keynesplein 9
, The Netherlands
Cert No: CE 800492

Michael & Associates, Inc. (Notified Body No.:)
2766 W. College Ave Suite 1
PA 16801, United States

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m^3)	EAN13	DUN14
PW40RER	Red	60.0	40.0	40.0	0.1720	0.0960	5036108134656	15036108636201

PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002

PW40/PS40		SNR 27.6dB		H:29.2	M:25.4	L:17.9		
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B	Mean Attenuation (dB)	18.1	15.0	18.3	26.8	37.5	29.5	35.8	36.1
C	Standard Deviation (dB)	4.1	2.7	3.3	2.0	4.1	2.9	3.3	5.8
D	Assumed Protection (dB)	14.0	12.3	15.0	24.8	33.4	26.6	32.5	30.3

PW40RER